

InSight[®] 5 Diff Retic

5 Part Differential Laser Haematology Analyser with Reticulocytes



**DUAL LASER
IMPEDANCE TECHNOLOGY.**

"PASSIONATE ABOUT LABORATORY DIAGNOSTICS"

**WOODLEY
EQUIPMENT COMPANY LTD.**

InSight[®] 5 Diff Retic

A True 5 Part Differential Laser Haematology Analyser including Reticulocytes

The InSight™ 5 Diff Retic Haematology Analyser is a fully automated multi-species analyser ideal for in-practice use. It uses Smart Software which automates all maintenance procedures. Quality control is performed on each blood sample using the combination of Laser, Impedance and Hb LED technology. During cellular analysis, impedance, the 'Gold Standard', is used for counting and sizing each cell while 'State of the Art' Laser technology is used for intracellular complexity and lobularity measurements.



Uses Dual Laser and Impedance Technology

FEATURES

- Compact, benchtop size
- Small sample size - 20µl whole blood
- True 31 parameter system
- 2 minute analysis time
- Reticulocytes on every sample
- Quick and easy operation
- Over 80 species on board
- 5-part differential with additional reticulocytes, band neutrophils & NRBC
- 2 new Retic measurements for maturity index and anisocytosis
- Touch screen
- Low maintenance
- Results transmitted via InSight p-LINK to Practice Management Systems

PARAMETERS

White Blood Cells		Red Blood Cells	
WBC		RBC	Retics#*
NE#	NE%	Hb	Retics%*
LY#	LY%	HCT	RDW
MO#	MO%	MCV	RSD
EO#	EO%	MCH	NRBC#*
BA#	BA%	MCHC	NRBC%*
BAND#	BAND%	MCVr	RDWr
Platelets		Printed WBC, RBC,	
PLT	PDW	PLT Cyotgrams	
MPV	PCT	*certain species only	

PRECISION

Parameter	Range	%CV
WBC	6.0 – 15.0 x 10 ³ µl	3.0
RBC	3.00 – 6.00 x 10 ⁶ µl	3.0
Hb	10.0 – 18.0 g/dL	3.0
MCV	50.0 – 70.0 fL	3.0
PLT	200 – 500 x 10 ³ µl	3.0
MPV	5.0 – 20.0 fL	3.0
RDW	12.0 – 15.0%	3.0

Methods and Technologies

- Laser Light Scatter
- Focussed Flow Impedance

User Interface

- Touch screen
- Single screen display of results
- One button sample aspiration

Sample Analysis Characteristics

- Onboard diluents dispenser
- Automatic probewash
- Patient ID
- Single button operation

LINEARITY

Parameter	Linearity Range
WBC	0.0 – 220.0 x 10 ³ µl
RBC	0.0 – 20.00 x 10 ⁶ µl
Hb	0.0 – 34.0 g/dL
PLT	0.0 – 5000 x 10 ³ µl

Throughput

- 30 samples per hour

Carryover

- High to low carryover is less than or equal to 2%

Host Communication

- RS232 port

+44 (0) 1204 669033 (Option 1)

sales@woodleyequipment.com

www.woodleyequipment.com

Old Station Park Buildings
St. John Street
Horwich
Bolton
Lancashire
BL6 7NY
UK

**"PASSIONATE ABOUT
LABORATORY DIAGNOSTICS"**

**WOODLEY
EQUIPMENT COMPANY LTD.**